

Écrans TACTILES

L'ÉCRAN TACTILE DE SIGNALISATION NUMÉRIQUE INTERACTIVE CRÉE UN FLUX NATUREL D'INFORMATIONS ENTRE L'UTILISATEUR ET L'ÉCRAN TACTILE.

CET ÉCRAN TACTILE INTÈGRE UN PANNEAU LCD DE SIGNALISATION NUMÉRIQUE POUR DES PERFORMANCES D'AFFICHAGE SUPÉRIEURES ET UNE SÉRIE DE MODULES INFORMATIQUES DE SIGNALISATION NUMÉRIQUE.

LES MODULES INFORMATIQUES SONT CONÇUS POUR SE GLISSER DANS UNE BAIE À L'ARRIÈRE DE L'ÉCRAN, SANS AUCUN EFFET SUR LA FORME DE L'ÉCRAN ET NE NÉCESSITANT AUCUN CÂBLAGE SUPPLÉMENTAIRE, TRANSFORMANT IMMÉDIATEMENT VOTRE ÉCRAN TACTILE DE SIGNALISATION NUMÉRIQUE INTERACTIVE EN UN ORDINATEUR TACTILE TOUT-EN-UN DE SIGNALISATION NUMÉRIQUE INTERACTIVE.



- * Utilisation en mode portrait ou paysage
- * Equipé de haut-parleurs de 2x10 watt (activés si nécessaire)
- * MTBF de 50 000 heures, conçu pour fonctionner 24/7
- * **Protection des câbles**, pas d'accès possible du public
- * Conforme aux tests de lâcher de balles UL-60950 et CSA C22.2 No. 60950 (balle de 0,5 kg et 50 mm de diamètre lâchée d'une hauteur de 1,3 m)

| | | | |
|------------------------------|---|---|---|
| MODÈLE | 32" | 42" | 46" |
| ÉCRAN | 31.5" diagonal, active matrix TFT LCD | 42.0" diagonal, Active matrix TFT LCD | 46.0" diagonal, Active matrix TFT LCD |
| ASPECT RATIO | 16:9 | 16:9 | 16:9 |
| SURFACE D'AFFICHAGE ACTIVE | Horizontal: 27.5» (698mm) Vertical: 15.4» (392mm) | Horizontal: 36.6» (930 mm) Vertical: 20.6» (523 mm) | Horizontal: 40.1» (1018 mm) Vertical: 22.5» (573 mm)w |
| RÉSOLUTION | 1366x768 | 1920x1080 | 1920x1080 |
| AUTRES RÉOLUTIONS SUPPORTÉES | 640x480 60Hz 720x480 60Hz 720x576 50Hz 800x600 56, 60Hz 1024x768 60Hz 1280x720 50, 60Hz 1280x960 60Hz 1280x1024 60Hz 1360x768 60Hz (does not scale; image is centered on panel and the remaining active area is filled with black) 1366x768 60Hz | 640x480 60Hz 720x480 60Hz 720x576 50Hz 800x600 56, 60Hz 1024x768 60Hz 1280x720 50, 60Hz 1280x960 60Hz 1280x1024 60Hz 1360x768 60Hz 1366x768 60Hz 1440x900 60Hz 1680x1050 60Hz 1920x1080 50, 60Hz | 640x480 60Hz 720x480 60Hz 720x576 50Hz 800x600 56, 60Hz 1024x768 60Hz 1280x720 50, 60Hz 1280x960 60Hz 1280x1024 60Hz 1360x768 60Hz 1366x768 60Hz 1440x900 60Hz 1680x1050 60Hz 1920x1080 50, 60Hz |
| COULEURS | 16.7 million | 16.7 million | 16.7 million |
| LUMINOSITÉ | LCD panel: 450nits with APR: 405nits | LCD panel: 700 nits with APR: 600 nits | LCD panel: 450 nits with APR: 405 nits |
| TEMPS DE RÉPONSE | 20 msec | 6.5 msec | 16 msec |
| ANGLES DE VUE | Horizontal: ±89° or 178° total Vertical: ±89° or 178° total | Horizontal: ±89° or 178° total Vertical: ±89° or 178° total | Horizontal: ±89° or 178° total Vertical: ±89° or 178° total |
| TAUX DE CONTRASTE | 3500:1 | 3500:1 | 3500:1 |
| ON-SCREEN DISPLAY (OSD) | <p>Controls : Menu, Up, Down, Select</p> <p>Settings : Brightness, Contrast, Clock, Phase, Auto-Adjust, H-position, V-position, Maintain Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, Mounting, OSD H-Position, OSD V-Position, Volume, Mute, Recall Defaults, Video Source, Audio Source</p> <p>Languages : English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese</p> <p>Lockouts : OSD, Power Accessible through switches on the rear, or through the standard Elo OSD control box..</p> | <p>Controls : Menu, Up, Down, Select, Power</p> <p>Settings : Brightness, Contrast, Clock, Phase, Auto-Adjust, H-position, V-position, Maintain Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, Mounting, OSD H-Position, OSD V-Position, Volume, Mute, Recall Defaults, Video Source, Audio Source</p> <p>Languages : English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese</p> <p>Lockouts : OSD, Power Accessible through switches on the rear, or through the standard Elo OSD control box.</p> | <p>Controls : Menu, Up, Down, Select, Power</p> <p>Settings : Brightness, Contrast, Clock, Phase, Auto-Adjust, H-position, V-position, Maintain Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, Mounting, OSD H-Position, OSD V-Position, Volume, Mute, Recall Defaults, Video Source, Audio Source</p> <p>Languages : English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese</p> <p>Lockouts : OSD, Power Accessible through switches on the rear, or through the standard Elo OSD control box.</p> |

